Product Data Sheet

BKPA-POA 80G

Light duty fixed castor, with top plate fitting, nylon wheel

EAN 4047526576974
ID 576975
Customs tariff number 87169090

Made in Germany



Bracket: BKPA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: POA series
- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour black

Other features:
- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C

Technical data:


Wheel Ø (D)		80 mm
Wheel width		32 mm
Load capacity at 3 km/h		120 kg
Load capacity (static)		300 kg
Bearing type		plain bore
Total height (H)		111 mm
Mounting type		top plate
Plate size		90 x 66 mm
Bolt hole spacing		75 x 45 / 61 x 51 mm
Bolt hole Ø		8.5 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		70 Shore D
Unit weight		0.3 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Tread and tyre hardness
■■■■■ 70 Shore D

Rolling resistance
■■■■■ excellent

Wear resistance
■■■□□ good

Operating noise / floor surface preservation
■■□□□ satisfactory



Product references



Corresponding swivel castor LKPA-POA 80G



Wheel used POA 80/12G