Product Data Sheet

BKRA-POA 150G

Light duty fixed castor, with bolt hole, nylon wheel

EAN 4047526108656
ID 673335
Customs tariff number 87169090

Made in Germany



Bracket: BKRA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: POA series
- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour black

Other features:
- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C

Technical data:


Wheel Ø (D)		150 mm
Wheel width		32 mm
Load capacity at 3 km/h		110 kg
Load capacity (static)		275 kg
Bearing type		plain bore
Total height (H)		182 mm
Plate Ø		57 mm
Bolt hole		13 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		70 Shore D
Unit weight		0.5 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Tread and tyre hardness
■■■■■ 70 Shore D

Rolling resistance
■■■■■ excellent

Wear resistance
■■■□□ good

Operating noise / floor surface preservation
■■□□□ satisfactory



Product references



Corresponding swivel castor LKRA-POA 150G



Wheel used POA 150/12G