Product Data Sheet

BKRA-TPA 126KF

Light duty fixed castor, with bolt hole, wheel, with thermoplastic rubber tread, with polypropylene wheel centre, with synthetic thread guard, large



EAN 4047526575137
ID 575134
Customs tariff number 87169090

Made in Germany

Bracket: BKRA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: TPA series
- tread: high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A, colour grey, non-marking, oil containing
- wheel centre: high-quality polypropylene, impact resistant, colour silver grey

Other features:
- with synthetic thread guard, large
- very high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C
- tread contains oil, may stain sensitive surfaces. alternatives: series VPA, VPP, POES, POEV, PATH

Technical data:


Wheel Ø (D)		125 mm
Wheel width		32 mm
Load capacity at 3 km/h		120 kg
Load capacity (static)		300 kg
Bearing type		ball bearing (C)
Total height (H)		158 mm
Mounting type		bolt hole
Plate Ø		57 mm
Bolt hole		13 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tyre hardness		85 Shore A
Unit weight		0.5 kg
Non-marking		✓
Non-staining		✗
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Tread and tyre hardness
■■■□□ 85 Shore A

Rolling resistance
■■■■□ very good

Wear resistance
■■□□□ satisfactory

Operating noise / floor surface preservation
■■■□□ good



Product references



Corresponding swivel castor LKRA-TPA 126KF



Wheel used TPA 126/8KF