Product Data Sheet

BKRA-VPA 126G

Light duty fixed castor, with bolt hole, wheel, with solid rubber tyres, with synthetic rim

EAN 4047526321369
ID 321364
Customs tariff number 87169090

Made in Germany



Bracket: BKRA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: VPA series
- tyre: high-quality solid rubber, hardness 80 Shore A, colour grey, non-marking, non-staining
- rim: high-quality nylon 6 or polypropylene in the electrically conductive version "-EL", impact resistant, colour black

Other features:
- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C

Technical data:


Wheel Ø (D)		125 mm
Wheel width		32 mm
Load capacity at 3 km/h		120 kg
Load capacity (static)		300 kg
Bearing type		plain bore
Total height (H)		158 mm
Plate Ø		57 mm
Bolt hole		13 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tyre hardness		80 Shore A
Unit weight		0.6 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Tread and tyre hardness
■■■□□ 80 Shore A

Rolling resistance
■■■□□ good

Wear resistance
■□□□□ sufficient

Operating noise / floor surface preservation
■■■■□ very good



Product references



Corresponding swivel castor LKRA-VPA 126G



Wheel used VPA 126/12G