Product Data Sheet

BPA-PATH 75KF

Light duty fixed castor, with top plate fitting, wheel, with thermoplastic polyurethane tread, with nylon wheel centre, with synthetic thread guard, large



EAN 4047526117450
ID 757003
Customs tariff number 83022000

Made in Germany

Bracket: BPA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: PATH series
- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour silver grey


Other features:
- with synthetic thread guard, large
- very high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +35 °C

Tread and tyre hardness
94 Shore A

Rolling resistance
very good

Wear resistance
very good

Operating noise / floor surface preservation
good



Technical data:

Wheel Ø (D)		75 mm
Wheel width		25 mm
Load capacity at 3 km/h		75 kg
Load capacity (static)		190 kg
Bearing type		ball bearing (C)
Total height (H)		100 mm
Mounting type		top plate
Plate size		60 x 60 mm
Bolt hole spacing		38 x 38 / 48 x 48 mm
Bolt hole Ø		6.2 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tyre hardness		94 Shore A
Unit weight		0.3 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Product references



Corresponding swivel castor LPA-PATH 75KF



Wheel used PATH 75/6KF