Product Data Sheet

BRA-POA 75G

Light duty fixed castor, with bolt hole, nylon wheel



EAN 4047526274368
ID 274365
Customs tariff number 83022000

Made in Germany

Bracket: BRA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: POA series
- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour black

Other features:
- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C

Technical data:


Wheel Ø (D)		75 mm
Wheel width		23 mm
Load capacity at 3 km/h		75 kg
Load capacity (static)		190 kg
Bearing type		plain bore
Total height (H)		98 mm
Plate Ø		43 mm
Bolt hole		11 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		70 Shore D
Unit weight		0.1 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Tread and tyre hardness
70 Shore D

Rolling resistance
excellent

Wear resistance
good

Operating noise / floor surface preservation
satisfactory



Product references



Corresponding swivel castor LRA-POA 75G



Wheel used POA 75/8G