Product Data Sheet

LDA-PATH 75KF

Light duty twin wheel swivel castor, with top plate fitting, wheel, with thermoplastic polyurethane tread, with nylon wheel centre, with synthetic thread guard, large

EAN 4047526117696
ID 757037
Customs tariff number 83022000

Made in Germany



Bracket: LDA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- pressed swivel head

Wheel: PATH series
- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour silver grey


Other features:
- with synthetic thread guard, large
- very high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +35 °C

Tread and tyre hardness
94 Shore A

Rolling resistance
very good

Wear resistance
very good

Operating noise / floor surface preservation
good



Technical data:

Wheel Ø (D)		75 mm
Wheel width		25 mm
Number of wheels		2
Load capacity at 3 km/h		100 kg
Load capacity (static)		250 kg
Bearing type		ball bearing (C)
Total height (H)		101 mm
Plate size		60 x 60 mm
Bolt hole spacing		40 x 40 / 46 x 46 mm
Bolt hole Ø		6.2 mm
Offset (F)		34 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tyre hardness		94 Shore A
Unit weight		0.6 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗

Suitable for machine washing		✕

Product references



Corresponding standard locking LDA-PATH 75KF-FI



Wheel used PATH 75/6KF