Product Data Sheet

LDA-TPA 75KF

Light duty twin wheel swivel castor, with top plate fitting, wheel, with thermoplastic rubber tread, with polypropylene wheel centre, with synthetic thread guard, large

EAN 4047526574635
ID 574632
Customs tariff number 83022000

Made in Germany



Bracket: LDA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- pressed swivel head

Wheel: TPA series
- tread: high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A, colour grey, non-marking, oil containing
- wheel centre: high-quality polypropylene, impact resistant, colour silver grey


Other features:
- with synthetic thread guard, large
- very high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C
- tread contains oil, may stain sensitive surfaces. alternatives: series VPA, VPP, POES, POEV, PATH


Tread and tyre hardness
85 Shore A

Rolling resistance
very good

Wear resistance
satisfactory

Operating noise / floor surface preservation
good





Technical data:

Wheel Ø (D)		75 mm
Wheel width		25 mm
Number of wheels		2
Load capacity at 3 km/h		100 kg
Load capacity (static)		250 kg
Bearing type		ball bearing (C)
Total height (H)		101 mm
Mounting type		top plate
Plate size		60 x 60 mm
Bolt hole spacing		40 x 40 / 46 x 46 mm
Bolt hole Ø		6.2 mm
Offset (F)		34 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tyre hardness		85 Shore A
Unit weight		0.6 kg
Non-marking		✓
Non-staining		✗
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗

Suitable for autoclaves		✕
Suitable for machine washing		✕

Product references



Corresponding standard locking LDA-TPA 75KF-FI



Wheel used TPA 75/6KF