Product Data Sheet

LKPA-PATH 101G

Light duty swivel castor, with top plate fitting, wheel, with thermoplastic polyurethane tread, with nylon wheel centre

EAN 4047526125790
ID 846966
Customs tariff number 87169090

Made in Germany



Bracket: LKPA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: PATH series
- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour silver grey

Other features:
- very high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +35 °C

Technical data:


Wheel Ø (D)		100 mm
Wheel width		32 mm
Load capacity at 3 km/h		120 kg
Load capacity (static)		300 kg
Bearing type		plain bore
Total height (H)		136 mm
Mounting type		top plate
Plate size		90 x 66 mm
Bolt hole spacing		75 x 45 / 61 x 51 mm
Bolt hole Ø		8.5 mm
Offset (F)		40 mm
Temperature resistance min		-25 °C
Temperature resistance max		70 °C
Tread and tyre hardness		94 Shore A
Unit weight		0.7 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗


Tread and tyre hardness
94 Shore A

Rolling resistance
very good

Wear resistance
very good

Operating noise / floor surface preservation
good





Suitable for machine washing		✕

Product references



Corresponding standard locking LKPA-PATH 101G-FI



Corresponding fixed castor BKPA-PATH 101G



Wheel used PATH 101/12G