Product Data Sheet

LKRA-TPA 126KF

Light duty swivel castor, with bolt hole fitting, wheel, with thermoplastic rubber tread, with polypropylene wheel centre, with synthetic thread guard, large

EAN 4047526575076
ID 575076
Customs tariff number 87169090

Made in Germany



Bracket: LKRA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: TPA series
- tread: high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A, colour grey, non-marking, oil containing
- wheel centre: high-quality polypropylene, impact resistant, colour silver grey


Other features:
- with synthetic thread guard, large
- very high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C
- tread contains oil, may stain sensitive surfaces. alternatives: series VPA, VPP, POES, POEV, PATH


Tread and tyre hardness
85 Shore A

Rolling resistance
very good

Wear resistance
satisfactory

Operating noise / floor surface preservation
good





Technical data:

Wheel Ø (D)		125 mm
Wheel width		32 mm
Load capacity at 3 km/h		120 kg
Load capacity (static)		300 kg
Bearing type		ball bearing (C)
Total height (H)		158 mm
Mounting type		bolt hole
Plate Ø		57 mm
Bolt hole		13 mm
Offset (F)		40 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tyre hardness		85 Shore A
Unit weight		0.6 kg
Non-marking		✓
Non-staining		✗
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Suitable for autoclaves		✗

Suitable for machine washing		✕

Product references



Corresponding standard locking LKRA-TPA 126KF-FI



Corresponding fixed castor BKRA-TPA 126KF



Wheel used TPA 126/8KF