Product Data Sheet

LRA-POA 35G-ES

Light duty swivel castor, with bolt hole fitting, with plug-in pin, nylon wheel

EAN 4047526431327
ID 431320
Customs tariff number 83022000

Made in Germany



Bracket: LRA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: POA series
- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour black

Other features:
- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C

Technical data:


Wheel Ø (D)		35 mm
Wheel width		25 mm
Load capacity at 3 km/h		75 kg
Load capacity (static)		190 kg
Bearing type		plain bore
Total height (H)		50 mm
Mounting type		plug-in pin
Pin Ø		11 mm
Pin length		30.5 mm
Offset (F)		15 mm
Temperature resistance min		-25 °C
Temperature resistance max		80 °C
Tread and tyre hardness		70 Shore D
Unit weight		0.2 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗


Tread and tyre hardness
■■■■■ 70 Shore D

Rolling resistance
■■■■■ excellent

Wear resistance
■■■□□ good

Operating noise / floor surface preservation
■■□□□ satisfactory





Product references



Corresponding standard locking LRA-POA 35G-RA-ES



Wheel used POA 35/8G