Product Data Sheet

LRA-TPA 100G-ES

Light duty swivel castor, with bolt hole fitting, with plug-in pin, wheel, with thermoplastic rubber tread, with polypropylene wheel centre

EAN 4047526614324
ID 614321
Customs tariff number 83022000

Made in Germany



Bracket: LRA series
- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: TPA series
- tread: high-quality thermoplastic rubber-elastomer (TPE), hardness 85 Shore A, colour grey, non-marking, oil containing
- wheel centre: high-quality polypropylene, impact resistant, colour silver grey


Other features:
- very high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +60 °C, reduced load capacity over +30 °C
- tread contains oil, may stain sensitive surfaces. alternatives: series VPA, VPP, POES, POEV, PATH


Tread and tyre hardness
85 Shore A

Rolling resistance
very good

Wear resistance
satisfactory

Operating noise / floor surface preservation
good





Technical data:

Wheel Ø (D)		100 mm
Wheel width		25 mm
Load capacity at 3 km/h		70 kg
Load capacity (static)		175 kg
Bearing type		plain bore
Total height (H)		121 mm
Mounting type		plug-in pin
Pin Ø		11 mm
Pin length		30.5 mm
Offset (F)		33 mm
Temperature resistance min		-20 °C
Temperature resistance max		60 °C
Tread and tyre hardness		85 Shore A
Unit weight		0.3 kg
Non-marking		✓
Non-staining		✗
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Product references



Corresponding standard locking LRA-TPA 100G-FI-ES



Wheel used TPA 100/8G