PATH 50/6KF

Wheel, with thermoplastic polyurethane tread, with nylon wheel centre, with synthetic thread guard, large

EAN 4047526116958
ID 755795
Customs tariff number 83022000

Made in Germany



Tread:
- high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A
- low rolling and swivel resistance
- high abrasion resistance
- colour dark grey, non-marking, non-staining
- chemically-bonded inseparable connection with the wheel centre

Wheel centre:
- high-quality nylon 6, impact resistant
- colour silver grey

Other features:
- with synthetic thread guard, large
- very high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +35 °C

Technical data:

Wheel Ø (D)		50 mm
Wheel width		19 mm
Load capacity at 3 km/h		75 kg
Load capacity (static)		190 kg
Bearing type		ball bearing (C)
Axle bore Ø (d)		6 mm
Hub keyway (T1)		23 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tyre hardness		94 Shore A
Unit weight		0.1 kg
Non-marking		✓
Non-staining		✓
Antistatic		✗
ESD		✗
Electrically conductive		✗
Corrosion-resistant		✗
Heat-resistant		✗
Tread hydrolysis-resistant		✗
Suitable for autoclaves		✗

Tread and tyre hardness
94 Shore A

Rolling resistance
very good

Wear resistance
very good

Operating noise / floor surface preservation
good

